







Uses

Bitu QPR Binder is formulated mixture of bitumen, binder enhancers and special additives designed to be blended with selected aggregates in the manufacture of cold asphalt mix for general road surfacing and repair.

Bitu QPR Binder is ready to use modified bitumen especially design for quick repair of asphalt surface just required addition of graded aggregates to prepare cold mix asphalt.

Benefits

- **Cold Applied:** No heating is required during preparation of mix.
- **Equipment**: No specialized equipment required.
- Quick Traffic Allow: Minimal disruption to traffic, roads can be opened to light traffic within 10 – 12 hours after compaction; higher trafficked areas can be opened within 24 hours.
- Save Labor Cost: save labor fast application
- Reduce Permeability: Improve Water proofing
- Compaction: Easy compaction.

Description

Bitu QPR Binder* is a blend of bitumen and special additives, especially design for cold mix asphalt for the repairing of asphalt surface.

Technical support

Pakistan Bitumen Company provides a technical advisory service for on-site assistance and advice on selection of products.

Properties

Appearance	: Black liquid
Softening point of residue °C	: 48 - 50
Viscosity @ 50 °C cp	: 160
Penetration of Residue	: 60/70

Standard compliance

ASTM D-2027

Dosage

Dosage of **Bitu QPR Binder** is 5-7 % by weight of aggregate.

Preparation & Application

Ensure that the base layer is well compacted to the required density and is free from loose material and standing water.

Apply **Bituaqua Tack Coat** as primer for the bonding between base and **Bitu QPR Binder** mix.

Place the prepared cold asphalt mix at regular intervals and level to the required thickness.

Properly compact the cold mix using a roller, water the drums to assist with sticking of material.

Health and safety

For further information consult the Material Safety Data Sheet available for this product

Estimating - packaging

Bitu QPR Binder* is available in 218 kg. Drums and bulk supply.







Additional Information:

Pakistan Bitumen Company manufactures a wide range of asphalt pavement related products, which include:

- Bituaqua Prime Coat* (Anionic & Cationic)
- Bituaqua Tack Coat*
- Bituaqua Seal Coat*
- Bituaqua ST*
- Bitu Cutback*
- Bitu Polymer*
- Bitu PG*

•

For further details about the above products, please contact to our sales offices on below mentioned contact numbers or send your inquiry by email.

* Denotes the trademark registered

REGIONAL SALES OFFICES IN PAKISTAN:

Pakistan Bitumen Company Subsidiary of Fospak (Pvt) Ltd.

Head Office 702, Business Avenue, Block-6, PECHS. Shahra-e-Faisal,

Karachi, Pakistan Tel # +92-21-34528477,34529859 Fax # +92-21-34522436

Email info.khi@fospak.com.pk

Lahore Sales Office

2nd Floor Sarwar Shaheed Plaza,

Cavalry Ground, Main Boulevard, Lahore Cantt, Lahore. Tel # +92-42-36675773

Fax # +92-42-36675838 Email info.lhr@fospak.com.pk **Rawalpindi Sales Office**

1st Floor, Al-Harmain Plaza, Main Murree Road, Rawalpindi

Tel # +92-51-9290592 Fax # +92-51-9290590 Email info.isb@fospak.com.pk

Important note

PBC products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst PBC endeavours to ensure that the technical information on this data sheet is correct at the time of printing, it is the customer's responsibility to satisfy himself, by checking with the company that this information is still current at the time of use, that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended. Because PBC has no control over the conditions of use of its products, all recommendations or suggestions regarding the use of these products are made without guarantee.