



Protect Environment

Always Think

Green



Bituaqua Polymer Tack Coat*

Bitumen emulsion polymer tack coat

Uses

Tack coat is a brownish-black emulsion of asphalt that is applied to the prepared, existing asphalt or concrete surface prior to placing new hot mix asphalt. It creates bond between two asphaltic layers and concrete, it helps to prevent water intrusion that can create potholes in asphalt works.

Advantages

- Fast dry time vs. cutback asphalt
- Easy and uniform spray
- Enhances structural strength of layers
- Prevents lateral movement of structural layers
- Water resistant and enhances shedding of water
- Provides an impervious layer to prevent water ingress from the possible water table below
- Creates an excellent bond between existing surface and a new course of asphalt
- Environmental friendly
- No specified temperatures to spray
- Non hazardous

Compliance to ASTM / BS / AASHTO Standards

ASTM D140, ASTM D244, ASTM D977, BS 434, AASHTO M-140, AASHTO D242-38

Description

Bituaqua Polymer Tack Coat* is a blend of bitumen, emulsifying agents, and modified SBS polymer; it is supplied as brown liquid, high-quality asphalt emulsion tack coat for pavement bonding applications. **Bituaqua Polymer Tack Coat** is a specially-designed product for ensuring a uniform and strong bond between layers of asphalt and concrete.

Properties

Appearance	: Brown liquid
Residue	: 53 ± 2 %
Saybolt Furol Viscosity	: 20 Sec. – 30 Sec. @ 25 °C
Particle size	: 5 – 6 microns
Softening point	: 55 °C ± 2
Settlement 5 days	: < 3%
Grade	: Rapid Set Medium Set
Setting time at 30 °C	: 2 – 5 Hours. 4 – 6 Hours

Surface Preparation


Clean the surface with broom or with air pressure make sure that the surface is free from dust and loose particles.

Application

Bituaqua Polymer Tack Coat* should be applied using well-calibrated distributors to spread as evenly as possible to achieve optimum coverage. The rate of application is 0.20 – 0.65 Kg. / m². Do a test area to check the coverage.

Technical support

Pakistan Bitumen Company provides a technical advisory service for on-site assistance and advice on selection of right products, as per site conditions.



Precaution / Limitation

Bituaqua Polymer Tack Coat* shall not be applied when the ambient temperature is below 5° C, or when rain is imminent.

Bituaqua Polymer Tack Coat* may be harmful to growing plants, since like any other oil, it seals pores and interferes with intake of carbon dioxide. Reasonable care should be taken to prevent spray on crops. Also, since the product is black, reasonable care should be taken to prevent spraying on buildings, fences, and other areas where dark stains are undesirable.

Avoid skin and eye contact, in case of contact, use plenty of water and seek medical advice, use the appropriate means if self-protection, the emulsion is nontoxic, it must not be disposed to surface and still water.

Bituaqua Polymer Tack Coat* does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes.

Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately do not induce vomiting.

Protect Environment

The primary pollutants of concern from asphalt paving operations are volatile organic compounds (VOC). Cutback asphalts are the major source of VOCs as only minor amounts of VOCs are emitted from emulsified asphalts and asphalt cements. VOC emissions from cutback asphalts result from the evaporation of the petroleum distillate used to liquefy the asphalt cement. VOC emissions can occur at both the job site and the mixing plant; however, the largest source of emissions was reported as from the road.

Asphalt emulsions are typically used in place of cutback asphalts to eliminate VOC emissions. The use of cutback asphalt is regulated in many jurisdictions to help reduce VOC emissions. Prohibitions on the use of cutback, either permanently or during certain times of the year, are common in jurisdictions that have either reached, or are nearing non-attainment for ozone requirements of the Clean Air Act.

Storage

Bituaqua Polymer Tack Coat* has a shelf life of 12 months provided the temperature is kept within the range of 5°C to 50°C. Should the temperature of the product fall outside this range then contact your local office for advice.

Freezing point: Approximately Below 0°C

Health and safety

For further information consult the Material Safety Data Sheet available for this product.

Fire

Bituaqua Polymer Tack Coat* is water base and non-flammable

Estimating – packaging

Bituaqua Polymer Tack Coat* is available in 218 kg. (Gross) Drums and bulk supply.

* Denotes the trademark registered

REGIONAL SALES OFFICES IN PAKISTAN:

Pakistan Bitumen Company Subsidiary of Fospak (Pvt) Ltd.

Head Office

702, Business Avenue,
Block-6, PECHS.
Shahra-e-Faisal,
Karachi, Pakistan
Tel # +92-21-34528477,34529859
Fax # +92-21-34522436
Email info.khi@fospak.com.pk

Lahore Sales Office

2nd Floor Sarwar Shaheed Plaza,
Cavalry Ground,
Main Boulevard,
Lahore Cantt, Lahore.
Tel # +92-42-36675773
Fax # +92-42-36675838
Email info.lhr@fospak.com.pk

Rawalpindi Sales Office

1st Floor, Al-Harain Plaza,
Main Murree Road,
Rawalpindi
Tel # +92-51-9290592
Fax # +92-51-9290590
Email info.isb@fospak.com.pk

Important note

PBC products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst PBC endeavours to ensure that the technical information on this data sheet is correct at the time of printing, it is the customer's responsibility to satisfy himself, by checking with the company that this information is still current at the time of use, that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended. Because PBC has no control over the conditions of use of its products, all recommendations or suggestions regarding the use of these products are made without guarantee.