



CONSTRUCTION CHEMISTRY

Mixing

When used at the mixing plant, Expanplast* Super40 should be added in the mixing water.

In some instances, e.g. addition to ready mix concrete on site, Expanplast* Super40 can be added directly in the truck mixer and mixed at maximum speed for an extra 5 minutes.

Dispensing

The correct quantity of Expanplast* Super40 should be measured by means of a recommended dispenser. The admixture should then be added to the concrete with the mixing water to obtain the best results. Contact Expanchem Fospak for advice regarding suitable equipment and its installation.

Estimating – packaging

Expanplast* Super40 is available in 210 litre drums and 1000 litre totes.

Storage

Expanplast* Super40 has a minimum shelf life of 12 months provided the temperature is kept within the range of 2°C to 50°C. Should the temperature of the product fall outside this range then contact Expanchem Fospak for advice.

Precautions

Health and safety

Expanplast* Super40 does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes.

Suitable protective gloves and goggles should be worn.

Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately - do not induce vomiting.

For further information consult the Material Safety Data Sheet available for this product.

Fire

Expanplast* Super40 is water based and non-flammable.

Cleaning and disposal

Spillages of Expanplast* Super40 should be absorbed onto sand, earth or vermiculite and transferred to suitable containers. Remnants should be hosed down with large quantities of water.

The disposal of excess or waste material should be carried out in accordance with local legislation under the guidance of the local waste regulatory authority.

* Denotes the trademark registered.

REGIONAL SALES OFFICES IN PAKISTAN:

Fospak (Pvt) Ltd.

Head Office

702, Business Avenue,
Block-6, PECHS., Shakra-e-Faisal,
Karachi, Pakistan.
Tel # +92-21-34528477, 34529859
Fax # +92-21-34522436
Email : info.khi@fospak.com.pk

Lahore Sales Office

2nd Floor Sarwar Shaheed Plaza,
Cavalry Ground,
Main Boulevard, Lahore Cantt,
Lahore, Pakistan.
Tel # +92-42-36675773
Fax # +92-42-36675838
Email : info.lhr@fospak.com.pk

Rawalpindi Sales Office

1st Floor,
Al-Harmain Plaza,
Main Murree Road,
Rawalpindi, Pakistan.
Tel # +92-51-39290592
Fax # +92-51-39290590
Email : info.isb@fospak.com.pk

Important note

Expanchem Fospak products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Expanchem Fospak endeavours to ensure that the technical information on this data sheet is correct at the time of printing, it is the customer's responsibility to satisfy himself, by checking with the company that this information is still current at the time of use, that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended. Because Expanchem Fospak has no control over the conditions of use of its products, all recommendations or suggestions regarding the use of these products are made without guarantee.

www.fospak.com